

Product Name	40" NARROW BEZEL LCD PANEL	46" NARROW BEZEL LCD PANEL	46" SUPER NARROW BEZEL LCD PANEL
Screen Size (active area)	40 inch	46 inch	46 inch
Bezel Size (mm)	12.5	12.5	Bottom: 2.4 Top 4.3
Aspect Ratio	16:9	16:9	16:9
Resolution	1920x1080	1920x1080	1920x1080 (WXGA)
Pixel Pitch (HxW mm)	0.648x0.648	0.7455x0.7455	0.7455x0.7455
Product Dimensions (mm)	524.2(W) x 911.7(H) x 98.7(D)	600.6(W) x1047.4(H) x 103(D)	579.84(W) x 1025.65(H) x 95.83(D)
Response Time	8ms	8ms	8ms
Displayable Colours	8 BIT,16.7M	8 BIT,16.7M	16.7M
Brightness	700cd/m ²	700cd/m ²	700cd/m ²
Contrast Ratio	1200:1	1200:1	3000:1
Colour Temperature	10000K	10000K	10000K
Viewing Angle	178 degrees	178 degrees	178 Degrees
Active Area	885.168(H) x 497.664(W)	1018.353(H) x 572.544(W)	1018.3(H) x 572.5(W)
Power Supply	AC 100V ~ 240V,50/60Hz,Universal +/- 10%	AC 100V ~ 240V,50/60Hz,Universal +/- 10%	100V ~ 240V(50/60Hz)
Power Consumption	250W typical normal operation	300W typical normal operation	Operate 200 Watt (Max 300 watt)
Power Management	VESA DPMS	VESA DPMS	VESA DPMS
Backlight Life	50000 hours	50000 hours	50000 hours
Recommended Resolution	1366 x 768	1366 x 768	1366 x 768
(PC) input	Video	1.0V p-p 75ohm	
		NTSC/PAL	
	VGA	0.7V p-p,75ohm	
		VGA60,SVGA60,XGA60,UXGA60 1280X720(60Hz),1360X768(60Hz),1920X1080(60Hz)	
	DVI	DVI VGA60,SVGA60,XGA60,SXGA60,UXGA60	
	RGB/HV	0.7V p-p,75ohm	
VGA60,SVGA60,XGA60,SXGA60,UXGA60 1280x720(60Hz),1360X768(60Hz),1920X1080(60Hz)			
YUV	ypbpr		
Protection glass	Anti Glare	Reflection Rate ≤0.5%	
Temperature	Operational	0-50°C	
	Storage	-20~70°C	
Humidity	Operational	20-80%	
	Storage	20-80%	